

QBTA: ON [ALT-F1/BB=60]

File Dynamics, Inc.

DPF

File Dynamics 19-Jul-13 11:18	FS — 10	BN 1349 SL 183/ 3440/	PJ: sn 2 PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30						
DL -27 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1090						
TS 12 TB 8.0					B PD: 44735-075 T1 9.5 2L/C 4.7 UA 1000	LP 0.00 ft LI 1.0
ACCEPT SQ-OFF FL-OFF PR-OFF						
contact File Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916						
<-AT:PIEZORESISTIVE						

UMX= 4.0 FMX= 62 AMX= 139
EMX= 0.2 MEX= 121 FUP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 44735

CALIBRATION FACTOR: 1090 GW

PAK (*5000) DATE: 19-July-13

PDA OPERATOR: *[Signature]*

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By AM on 19-July-13 CRC Value F657