

^CTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 02-Jul-13 12:56		FS —	BN 252	PJ: sn	TG F2 -- US
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s		10	SL 124/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -42 UT -1 PK 1 TM-PEAK		TS 12 B PD: 44582 LP 0.00 ft TB 8.0 TI 9.2 2L/C 4.7 VA 1000 UE 1022 LI 1.0			
F1 500 F2 213 A1 999 A2 1126					

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 2.7	FMX= 42	AMX= 80
EMX= 0.1	MEX= 82	FUP= 0.99



contact Pile Dynamics USA  
with your questions  
tel USA - 216 - 831- 6131  
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 44582

CALIBRATION FACTOR: 1126 G/Y

PAK (\*5000): \_\_\_\_\_ DATE: 2 Jul 13

PDA OPERATOR: LJG

<-AT:PIEZORESISTIVE

OP: dale Iver:4.05

AT:PIEZOELECTRIC->