

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

<b>Pile Dynamics</b> 21-Mar-14 10:02		FS — BN 53 10 SL 118/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN <del>KIPS=0.1</del> FR 20000 MB 30	TS 12 B PD: 47435-075 LP 0.00 ft TB 8.0 T1 9.3 2L/C 4.7 VA 1000 UE 1022 LI 1.0			
DL -41 UT -1 PK 1 TM-PEAK	F1 500 F2 213 A1 999 A2 1150			

ACCEPT  SQ-OFF  FL-OFF  PR-OFF  
 VMX= 3.7 FMX= 59 AMX= 110  
 EMX= 0.2 MEX= 115 FVP= 1.01



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

**ACCELEROMETER CALIBRATION** N.I.S.T. Traceable  
 SERIAL NUMBER: 47435  
 CALIBRATION FACTOR: 1150 G/V  
 PAK (\*5000): DATE: 21-Mar-14  
 PDA OPERATOR: Erik Smith

<-AT:PIEZORESISTIVE OP: erik [ver:4.05] AT:PIEZOELECTRIC->