

QBTA: ON TALT-F1/BB=60J

Pile Dynamics, Inc.

DPF

<b>Pile Dynamics</b> 10-Mar-14 09:15		FS — 10	BN 2644 SL 545/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPSCG 1 FR 20000 MB 30  DL -40 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 1160	TS 12 TB 8.0	B PD: 47439-075 T1 9.3 2L/C 4.7 VA 1000	LP 0.00 ft LI 1.0	UE 1022	

ACCENT SQ-OFF FL-OFF PR-OFF   contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	VMX= 4.0 FMX= 62 AMX= 120 EMX= 0.2 MEX= 121 FVP= 1.01  ACCELEROMETER CALIBRATION N.I.S.T. Traceable  SERIAL NUMBER: 47439 CALIBRATION FACTOR: 1160 G/v PAK-<*5000>: DATE: 10-Mar-14 PDA OPERATOR: Erik Saff OP: erik [ver:4.05]
<-AT:PIEZORESISTIVE	AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By E.S. on 3-10-14 CRC Value 61D6