


DPF

OBTA: ON IALT-F1/BB=601 Pile Dynamics, Inc. TG F2 -- US
A2 F2 3.3

File Dynamics 18-Sep-14 09:03	FS 10	BN 590 SL 209/ 3440/ 2	PJ: HOPBAR
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s			
JC 0.40 FM 1.00 UM 1.00			
EA/C 30.3 Ks/ft UN KIPS=0 FR 20000 MB 30			
DL -41 UT -1 PK 1 TM-PEAK			
F1 500 F2 213 A1 999 A2 1170	TS 12 TB 8.0	E B PD: 47448-075 T1 9.6 2L/C 4.7 VA 1000	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF	UMX= 4.1 FMX= 64 AMX= 129 EMX= 0.2 MEX= 125 FUP= 1.01
	ACCELEROMETER CALIBRATION N.I.S.T. Traceable
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	SERIAL NUMBER: 47448 CALIBRATION FACTOR: 1170 % DATE: 18SEP14 PAK (*5888): PDA OPERATOR: J.M.W.
<-AT:PIEZORESISTIVE	OP: Iaine Iver:4.051

Smart Sensor

Smart Chip Programmed By J.M.W. on 18SEP14 CRC Value D452