


QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 03-Apr-14 08:24 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 VM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -40 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1190	FS — BN 28 10 SL 128/ 3440/ 99 TS 12 B PD: 47463-075 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 1000 UE 1022 LI 1.0	PJ: PN: HOPBAR TG F2 -- US A2 F2 3.3
---	--	--

<input type="checkbox"/> ACCEPT <input type="checkbox"/> SQ-OFF <input type="checkbox"/> FL-OFF <input type="checkbox"/> PR-OFF  contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	UMX= 4.0 FMX= 61 AMX= 120 EMX= 0.2 MEX= 119 FVP= 1.00 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>47463</u> CALIBRATION FACTOR: <u>1190 G/v</u> PAK (*5000): _____ DATE: <u>3-Apr-14</u> PDA OPERATOR: <u>Erik Sver</u> OP: erik [ver:4.05]
--	---

<-AT:PIEZORESISTIVE

AT:PIEZOELECTRIC->