

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 16-Apr-14 08:53	FS — 10	BN 1456 SL 391/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 VM 1.00						
EA/C 30.3 Ks/ft UN KIPS 30.1						
FR 20000 MB 30						
DL -39 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1135						
TS 12 TB 8.0					B PD: 47558-075 T1 9.3 2L/C 4.7	LP 0.00 ft LI 1.0
ACCEPT SQ-OFF FL-OFF PR-OFF						
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916						

VMX= 3.8 FMX= 59 AMX= 110
EMX= 0.2 MEX= 115 FVP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 47558

CALIBRATION FACTOR: 1135 G/v

RAK (*5000): _____ DATE: 16-Apr-14

PDA OPERATOR: Erik S.

<-AT:PIEZORESISTIVE

OP: erik [ver:4.05]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By E.S. on 4-16-14 CRC Value 8C75