

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 03-Apr-15 08:46	FS — 10	BN 2642 SL 1184/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3			
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s							
JC 0.40 FM 1.00 VM 1.00							
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30							
DL -41 UT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 1170							
TS 12 TB 8.0					B PD: 47614-075 T1 9.6 2L/C 4.7 VA 1000 UE 1022	LP 0.00 ft LI 1.0	
VMX= 4.2 FMX= 66 AMX= 129 EMX= 0.3 MEX= 129 FVP= 1.00							
ACCEPT SQ-OFF FL-OFF PR-OFF							
ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 47614 CALIBRATION FACTOR: 1170%							
PAK (*5000): _____ DATE: 6APR15 PDA OPERATOR: <i>M. W. Wright</i>							


 contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

<-AT:PIEZORESISTIVE

OP: laine [ver:4.05]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By M.W. on 6APR15 CRC Value E476