


QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 03-Apr-15 00:37		FS 10	BN 2625 SL 1184/ 3440/ 99	P3: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30	TS 12 B PD: 47616-075 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.7 UA 1000 UE 1022 LI 1.0				
DL -41 UT -1 PK 1 TM-PEAK	UMX= 4.1 FMX= 64 AMX= 139 EMX= 0.2 MEX= 125 FVP= 1.00				
F1 500 F2 213 A1 999 A2 1165	ACCEPT SQ-OFF FL-OFF PR-OFF ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 47616 CALIBRATION FACTOR: 115% PAK-(x5000): DATE: 6APR15 PDA OPERATOR: J.M.W.				

  
 contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

<-AT:PIEZORESISTIVE

OP: laine [ver:4.05]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 6APR15 CRC Value CD6E