

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

<b>Pile Dynamics</b> 29-May-14 03:02	FS — 10	BN 1164 SL 255/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30	TS 12 B PD: 47624-075 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 VA 1000 VE 1022 LI 1.0			
DL -40 UT -1 PK, 1 ... TM-PEAK				
F1 500 F2 213 A1 999 A2 1115				

<p>contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916</p>	<p>UMX= 4.3 FMX= 66 AMX= 149 EMX= 0.3 MEX= 129 FVP= 1.01</p>
	<p>ACCELEROMETER CALIBRATION N.I.S.T. Traceable</p> <p>SERIAL NUMBER: 47624</p> <p>CALIBRATION FACTOR: 1115 g/v</p> <p>PAK (*5088): DATE: 29 MAY 14</p> <p>PDA OPERATOR: <i>M. Wang</i></p>
<p>&lt;-AT:PIEZORESISTIVE</p>	<p>OP: laine lver:4.051</p>
	<p>AT:PIEZOELECTRIC-&gt;</p>