

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 14-Apr-14 07:52		FS — 10	BN 997 SL 324/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPSE0/0 FR 20000 MB 30	TS 12 B PD: 47628-075 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 1000 UE 1022 LI 1.0				

	ACCEPT SQ-OFF FL-OFF PR-OFF	UMX= 4.0 FMX= 62 AMX= 120 EMX= 0.2 MEX= 121 FUP= 1.01
	contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 47628 Hammer CALIBRATION FACTOR: 1130 G/v PAK (<5000): DATE: 14-Apr-14 PDA OPERATOR: Erik S. [Signature]
<-AT:PIEZORESISTIVE		OP: erik [ver:4.05]

PIT-X Wireless Hammer Serial Number 30011-CC