

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 21-Mar-15 07:50	FS — 10	BN 2212 SL 1055/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPSE FR 20000 MB 30	TS 12 B PD: 50832-a075 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 1000 UE 1022 LI 1.0			
DL -39 UT -1 PK 1 TM-PEAK	F1 500 F2 213 A1 999 A2 1025			

ACCEPT SQ-OFF FL-OFF PR-OFF
 VMX= 4.3 FMX= 66 AMX= 139
 EMX= 0.3 MEX= 129 FUP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 50832
 CALIBRATION FACTOR: 1025%
 PAK-(x5000): DATE: 25MAR15
 PDA OPERATOR: J.M.W.

<-AT:PIEZORESISTIVE

OP: laine [ver:4.05]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 25MAR15 CRC Value D690