

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 22-May-17 02:02		FS — 10	BN 431 SL 556/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS* 16810 ft/s WC 17228 ft/s CAUTION					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30		TS 12 \$ B PD: 50898-a075 LP 0.00 ft TB 8.0 T1 9.5 2L/C 4.6 VA 1000 VE 1022 LI 1.0			
DL -41 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 985					

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

UMX= 4.8 FMX= 75 AMX= 139
 EMX= 0.3 MEX= 147 FUP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 50898

CALIBRATION FACTOR: 985%

PAK (*5000): DATE: 23 MAY 17

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: laine [ver:4.05]

[AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 23 MAY 17 CRC Value 2F53