

QBTA: DN [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

| | | | | |
|--|------------|-------------------------------|-------------------|--------------------------|
| Pile Dynamics 19-Apr-15 01:55 | FS — 10 | BN 3532 SL 1489 / 3440 / 2 | PJ: PN: HOPBAR | TG F2 -- US A2 F2 3.3 |
| LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s | | | | |
| JC 0.40 FM 1.00 UM 1.00 | | | | |
| EA/C 30.3 Ks/ft UN KIPS:30.1 FR 20000 MB 30 | | | | |
| DL -43 UT -1 PK 1 TM-PEAK | | | | |
| F1 500 F2 213 A1 999 A2 975 | | | | |
| TS 12 B PD: 50907-a075 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1022 LI 1.0 | | | | |

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.4 FMX= 67 AMX= 129
EMX= 0.3 MEX= 131 FUP= 0.99

contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 50907

CALIBRATION FACTOR: 975 %

PAK-50007: DATE: 22 APR 15

PDA OPERATOR: *M. Wright*

<-AT:PIEZORESISTIVE

OP: laine lver:4.051

AT:PIEZOELECTRIC->