

QBTA: ON [ALT-F1/BB=60] Pile Dynamics, Inc. DPF

Pile Dynamics 19-Apr-15 02:54	FS — 10	BN 3560 SL 1495/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30						
DL -43 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1010						
TS 12 TB 8.0					B PD: 51106-a075 T1 9.4 2L/C 4.7 VA 1000 UE 1022	LP 0.00 ft LI 1.0
UMX= 4.0 FMX= 61 AMX= 120 EMX= 0.2 MEX= 119 FUP= 1.00						
ACCEPT SQ-OFF FL-OFF PR-OFF 						
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916						
ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 51106 CALIBRATION FACTOR: 1010% PAK (*5000): DATE: 22APR15 PDA OPERATOR: M. W. W.						

<-AT:PIEZORESISTIVE OP: laine [ver:4.05] AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By M.W. on 22APR15 CRC Value BF1B