

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 19-Apr-15 02:57	FS — 10	BN 3566 SL 1495/ 3440/ 99	PJ: PN: HOPBAR	TG F2 A2 F2	-- US 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s							
JC 0.40 FM 1.00 VM 1.00							
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30							
DL -41 UT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 990							
TS 12 TB 8.0						B PD: 51142-a075 T1 9.5 2L/C 4.7 VA 1000 UE 1022	LP 0.00 ft LI 1.0

	UMX= 4.1 FMX= 63 AMX= 120 EMX= 0.2 MEX= 123 FVP= 1.00
	ACCEPT SQ-OFF FL-OFF PR-OFF ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 51142 CALIBRATION FACTOR: 990% PAK (*5000): DATE: 22APR15 PDA OPERATOR: <i>A.M.W.</i>

<-AT:PIEZORESISTIVE OP: Iaine Iver:4.051 [AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By A.M.W. on 22APR15 CRC Value D0AA