

QBTA: ON [ALT-F1/BB=60]

File Dynamics, Inc.

DPF

File Dynamics 28-Apr-15 04:12	FS — 10	BN 4246 SL 1716/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30						
DL -38 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 990						
TS 12 TB 8.0					B PD: 51169-a075 T1 9.6 2L/C 4.7 UA 1000 UE 1022	LP 0.00 ft LI 1.0

UMX= 4.1 FMX= 64 AMX= 129
EMX= 0.3 MEX= 125 FVP= 0.99

<p>contact File Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916</p>	<p>ACCELEROMETER CALIBRATION N.I.S.T. Traceable</p> <p>SERIAL NUMBER: <u>51169</u></p> <p>CALIBRATION FACTOR: <u>990%/v</u></p> <p>PAK (*5000): _____ DATE: <u>1 MAY 15</u></p> <p>PDA OPERATOR: <u>M. W. W.</u></p>
	<p>←-AT:PIEZORESISTIVE OP: laine [ver:4.05] [AT:PIEZOELECTRIC-→</p>

Smart Sensor

Smart Chip Programmed By S.M.W. on 1 MAY 15 CRC Value 766A