

OBTA: ON [ALT-F1/BB=601

Pile Dynamics, Inc.

DPF

File Dynamics 28-Apr-15 04:10	FS — 10	BN 4244 SL 1716/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN 20000 MB 30 FR 20000 MB 30	TS 12 B PD: 51170-a075 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1022 LI 1.0			
DL -41 UT -1 PK 1 TM-PEAK	F1 500 F2 213 A1 999 A2 965			

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.1 FMX= 63 AMX= 129  
 EMX= 0.2 MEX= 123 FUP= 0.99



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 51170

CALIBRATION FACTOR: 965%

PAK (\*5000): \_\_\_\_\_ DATE: 1MAY15

PDA OPERATOR: J.M.W.

<-AT:PIEZORESISTIVE

OP: Iaine Iver:4.051

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 1MAY15 CRC Value 4A17