

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics		FS	BN 437	PJ:	TG F2	-- US
26-May-15 03:21		10	SL 538/ 3440/ 99	PN: HOPBAR	A2 F2	3.3
LE	39.6 ft					
AR	1.7 in2					
EM	30000 Ksi					
SP	0.492 K/ft3					
WS	16810 ft/s					
WC	16862 ft/s					
JC	0.40					
FM	1.00					
UM	1.00					
EA/C	30.3 Ks/ft					
UN	KIPSEOFF					
FR	20000 MB 30					
DL	-41					
UT	-1					
PK	1 TM-PEAK					
F1	500					
F2	213					
A1	999					
A2	1025					
		TS 12	B PD: 51569-a075		LP 0.00 ft	
		TB 8.0	T1 9.6 2L/C 4.7 UA 1000 UE 1022		LI 1.0	

UMX= 4.3 FMX= 66 AMX= 129  
 EMX= 0.3 MEX= 129 FUP= 1.00

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 51569

CALIBRATION FACTOR: 1025%

PAK (x5000): DATE: 26MAY15

PDA OPERATOR: M. W. W. W.

<-AT:PIEZORESISTIVE

OP: Iain Iver:4.051

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By M.W. on 26MAY15 CRC Value 2504