

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 01-Nov-16 22:23	FS — 10	BN 185 SL 448/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3			
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s							
JC 0.40 FM 1.00 UM 1.00							
EA/C 30.3 Ks/ft UN (KIPS) 30 FR 20000 MB 30							
DL -31 UT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 1065							
TS 12 TB 8.0					B PD: 51576-a75 T1 9.6 2L/C 4.7	VA 1000	LP 0.00 ft LI 1.0
VE 1022							
ACCEPT SQ-OFF FL-OFF PR-OFF							
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916							

UMX= 4.7 FMX= 73 AMX= 159
 EMX= 0.3 MEX= 143 FUP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 51576
 CALIBRATION FACTOR: 1065 %
 PAK (*5000): DATE: 3NOV16
 PDA OPERATOR: [Signature]
 OP: laine [ver:4.05]

<-AT:PIEZORESISTIVE

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 3NOV16 CRC Value 0A22