


QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics		FS	BN 402	PJ:	TG F2	-- US
26-May-15 01:24		10	SL 525/ 3440/ 2	PN: HOPBAR	A2 F2	3.3
LE	39.6 ft					
AR	1.7 in2					
EM	30000 Ksi					
SP	0.492 K/ft3					
WS	16810 ft/s					
WC	16862 ft/s					
JC	0.40					
FM	1.00					
UM	1.00					
EA/C	30.3 Ks/ft					
UN	KIPS20.1					
FR	20000 MB 30					
DL	-41					
UT	-1					
PK	1 TM-PEAK					
F1	500					
F2	213					
A1	999					
A2	1055					
TS	12	B	PD: 51579-a075	LP	0.00 ft	
TB	8.0	T1	9.6	2L/C	4.7	VA 1000
				UE	1022	LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF	UMX= 4.5	FMX= 69	AMX= 149
	EMX= 0.3	MEX= 135	FVP= 0.99
 <p>contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916</p>	ACCELEROMETER CALIBRATION N.I.S.T. Traceable		
	SERIAL NUMBER: 51579		
	CALIBRATION FACTOR: 1055%/v		
	PAK (x5000):		DATE: 26MAY15
PDA OPERATOR: <i>J.M.W.</i>			
OP: laine [ver:4.05]		AT:PIEZOELECTRIC	

Smart Sensor

Smart Chip Programmed By J.M.W. on 26MAY15 CRC Value 93B4