


QBTA: ON IALT-F1/BB=601

File Dynamics, Inc.

DPF

File Dynamics 18-May-15 08:14	FS — 10	BN 280 SL 472/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3			
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s							
JC 0.40 FM 1.00 VM 1.00							
EA/C 30.3 Ks/ft UN KIPSK0.1 FR 20000 MB 30							
DL -39. UT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 965							
TS 12 TB 8.0					B PD: 51607-a075 T1 9.6 2L/C 4.7	VA 1000 UE 1022	LP 0.00 ft LI 1.0

 contact File Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	ACCEPT SQ-OFF FL-OFF PR-OFF UMV= 4.6 FMV= 70 AMV= 139 EMV= 0.3 MEX= 137 FVP= 0.99 ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 51607 CALIBRATION FACTOR: 965% PAK (*5000): DATE: 21MAY15 PDA OPERATOR: J.M.W. OP: laine [ver:4.05]
---	---

<-AT:PIEZORESISTIVE

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 21MAY15 CRC Value 3BF7