

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 28-Dec-17 23:58	FS — 10	BN 1271 SL 957/ 3440/ 4	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30						
DL -43 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 945						
TS 12 TB 8.0					B PD: 53153-a075 T1 9.6 2L/C 4.7 UA 1000	LP 0.00 ft LI 1.0
VE 1022						
UMX= 4.7 FMX= 73 AMX= 139 EMX= 0.3 MEX= 143 FVP= 1.01						
ACCEPT SQ-OFF FL-OFF PR-OFF						

contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>53153</u> CALIBRATION FACTOR: <u>945 g/v</u> PAK (*5000): _____ DATE: <u>3 JAN 18</u> PDA OPERATOR: <u>[Signature]</u>
<-AT:PIEZORESISTIVE	OP: laine [ver:4.05]
	AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By A.M.W. on 3 JAN 18 CRC Value 0407