

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 18-May-16 23:01		FS — 10	BN 54 SL 396/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16684 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN 41PS:0 FR 20000 MB 30	TS 12 B PD: 54871-b75 LP 0.00 ft TB 8.0 T1 9.6 2L/C 4.8 VA 1000 UE 1022 LI 1.0				
DL -43 UT -1 PK 1 TM-PEAK	F1 500 F2 213 A1 999 A2 940				

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 4.4 FMX= 69 AMX= 139
 EMX= 0.3 MEX= 135 FVP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION
 N.I.S.T. Traceable
 SERIAL NUMBER: 54871
 CALIBRATION FACTOR: 940%
 PAK < *5000 > : DATE: 19 MAY 16
 PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: Iaine Iver:4.051

PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 19 MAY 16 CRC Value 4446