

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 26-May-16 22:51	FS — 10	BN 395 SL 514/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 NS* 16810 ft/s RC 17228 ft/s CAUTION						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30						
DL -42 UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 915						
TS 12 TB 8.0					B PD: 54875-675 T1 9.6 2L/C 4.6 VA 1000	LP 0.00 ft LI 1.0
ACCEPT SQ-OFF FL-OFF PR-OFF						
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916						
UMx= 4.6 FMx= 70 AMx= 149 EMx= 0.3 MEx= 137 FUP= 0.98						
ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 54875 CALIBRATION FACTOR: 915 % PAK (*5000): DATE: 31MAY16 PDA OPERATOR: <i>[Signature]</i>						

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916

UMx= 4.6 FMx= 70 AMx= 149 EMx= 0.3 MEx= 137 FUP= 0.98

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 54875

CALIBRATION FACTOR: 915 %

PAK (*5000): DATE: 31MAY16

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: laine [ver:4.05]

PIEZOELECTRIC

Smart Sensor

Smart Chip Programmed By A.M.W. on 31MAY16 CRC Value D04B