


OBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

File Dynamics 08-Jun-16 23:36	FS — 10	BN 745 SL 647/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30				
DL -42 VT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 930				
TS 12 B PD: 54876-b75 TB 8.0 T1 9.4 2L/C 4.7 VA 1000 VE 1022 LP 0.00 ft LI 1.0				

 contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916	ACCEPT SQ-OFF FL-OFF PR-OFF UMX= 4.8 FMX= 74 AMX= 139 EMX= 0.3 MEX= 145 FUP= 0.98
	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 54876 CALIBRATION FACTOR: 930% PAK <#5000>: DATE: JUNE 16 PDA OPERATOR: <i>[Signature]</i>
<-AT:PIEZORESISTIVE OP: laine [ver:4.05] AT:PIEZOELECTRIC->	