

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics		FS	BN 247	PJ:	TG F2 -- US
06-Jan-17 04:00		10	SL 471/ 3440/ 99	PN: HOPBAR	A2 F2 3.3
LE	39.6 ft				
AR	1.7 in2				
EM	30000 Ksi				
SP	0.492 K/ft3				
WS	16810 ft/s				
WC	17043 ft/s				
JC	0.40				
FM	1.00				
VM	1.00				
EA/C 30.3 Ks/ft					
UN	KIPS=0.0				
FR	20000 MB 30				
DL	-40				
UT	-1				
PK	1 TM-PEAK				
F1	500	TS 12	B PD: 55733-b75	LP 0.00 ft	
F2	213	TB 8.0	T1 9.6 2L/C 4.7 UA 1000 UE 1022	LI 1.0	
A1	999				
A2	975				

UMX= 4.8 FMX= 74 AMX= 159
 EMX= 0.4 MEX= 145 FVP= 1.00

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 55733
 CALIBRATION FACTOR: 975%
 PAK (*5000): DATE: 6JAN17
 PDA OPERATOR: *Da*

<-AT:PIEZORESISTIVE

OP: laine [ver:4.05]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By A.M.W. on 6JAN17 CRC Value B407