

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics
25-Oct-17 08:08
LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16810 ft/s
WC 17043 ft/s

FS — BN 73 PJ:
10 SL 413/ 3440/ 2 PN: HOPBAR

TG F2 -- US
A2 F2 3.3

JC 0.40
FM 1.00
UM 1.00

EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 30

DL -42
UT -1
PK 1 TM-PEAK

F1 500
F2 213
A1 999
A2 985

TS 12 B PD: 55839-b755 LP 0.00 ft
TB 8.0 T1 9.6 2L/C 4.7 UA 1000 UE 1022 LI 1.0



ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

VMX= 4.5 FMX= 69 AMX= 159
EMX= 0.3 MEX= 135 FVP= 1.00

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 55839

CALIBRATION FACTOR: 985%/

PAK (*5000): DATE: 9 APR 18

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: laine [ver:4.05]

AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By J.M.W. on 9 APR 18 CRC Value 0FD9