

QBTA: ON [ALT-F1/BB=60]

File Dynamics, Inc.

DPF

File Dynamics 08-Nov-17 12:05	FS — 10	BN 572 SL 623/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3			
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s							
JC 0.40 FM 1.00 UM 1.00							
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30							
DL -42 UT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 1050							
TS 12 TB 8.0					B PD: 58405-b75 T1 9.5 2L/C 4.7	VA 1000 VE 1022	LP 0.00 ft LI 1.0

<p>contact File Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916</p>	UMX= 4.2 FMX= 66 AMX= 139 EMX= 0.3 MEX= 129 FVP= 1.01
	ACCEPT SQ-OFF FL-OFF PR-OFF ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: <u>58405</u> CALIBRATION FACTOR: <u>1050 %</u> PAK (<*5000): _____ DATE: <u>8/NOV17</u> PDA OPERATOR: <u>[Signature]</u>
<-AT:PIEZORESISTIVE OP: laine [ver:4.05]	AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By A.M.W. on 8/NOV17 CRC Value 4B41