

File Dynamics 28-Dec-06 13:54 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS* 16810 ft/s WC 17418 ft/s CAUTION JC 0.40 FM 1.00 VM 1.00 EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30 DL -38 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1015	FS — BN 599 SL 2642/ 3440/ 99 PJ: sn PN: HOPBAR TG F2 -- US A2 F2 3.3
TS 12 TB 8.0	B PD: a19985 T1 9.5 2L/C 4.6 VA 1000 UE 1022 LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

UMX= 4.4 FMX= 68 AMX= 139
 EMX= 0.3 MEX= 133 FUP= 0.99



contact File Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: A19985

CALIBRATION FACTOR: 1015 G/V

BAK (*5000): _____ DATE: 28-DEC-06

PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->