

Pile Dynamics 28-Dec-06 13:04		FS — 10	BN 495 SL 2641/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS* 16810 ft/s WC 17418 ft/s CAUTION					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS 0.1 FR 20000 MB 30					
DL -43 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1005		TS 12 TB 8.0	B PD: a19988 T1 9.4 2L/C 4.6	UA 1000 UE 1022	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
 VMX= 4.4 FMX= 66 AMX= 159
 EMX= 0.3 MEX= 129 FUP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: A19988
 CALIBRATION FACTOR: 1005 G/V
 PAK (*5000): _____ DATE: 28-DEC-06
 PDA OPERATOR: [Signature]

<-AT:PIEZORESISTIVE

OP: alex [ver:4.05]

AT:PIEZOELECTRIC->