

File Dynamics 28-Dec-06 13:17	FS — 10	BN 527 SL 2642/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3				
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS* 16810 ft/s WC 17418 ft/s CAUTION								
JC 0.40 FM 1.00 UM 1.00								
EA/C 30.3 Ks/ft UN KIPS=30.1 FR 20000 MB 30								
DL -37 VT -1 PK 1 TM-PEAK								
F1 500 F2 213 A1 999 A2 1000								
TS 12 TB 8.0					B PD: a19991 TI 9.4 2L/C 4.6	UA 1000	UE 1022	LP 0.00 ft LI 1.0
VMX= 4.5 FMX= 69 AMX= 149 EMX= 0.3 MEX= 135 FUP= 0.99								
ACCEPT SQ-OFF FL-OFF PR-OFF								
ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: A19991 CALIBRATION FACTOR: 1000 G/V PAK (*5800): DATE: 28-DEC-06 PDA OPERATOR: <i>[Signature]</i>								

contact File Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

←-AT:PIEZORESISTIVE OP: alex [ver:4.05] AT:PIEZOELECTRIC->