

File Dynamics 26-Aug-08 10:47	FS — 10	BN 4 SL 2742/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3			
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s							
JC 0.40 FM 1.00 UM 1.00							
EA/C 30.3 Ks/ft UN 41PS:0 FR 20000 MB 30							
DL -27 UT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 970							
TS 12 TB 8.0					B PD: a20009 T1 9.6 2L/C 4.7	UA 1000	LP 0.00 ft LI 1.0
<b>VE 1022</b>							
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916							
←-AT:PIEZORESISTIVE							

ACCEPT SQ-OFF FL-OFF PR-OFF  
 VMX= 4.0 FMX= 61 AMX= 149  
 EMX= 0.2 MEX= 119 FUP= 1.00

**ACCELEROMETER CALIBRATION** N.I.S.T. Traceable  
 SERIAL NUMBER: A20009  
 CALIBRATION FACTOR: 970 G/V  
 PAK (3000) DATE: 26-Aug-08  
 PDA OPERATOR: [Signature]  
 OP: alex [ver:4.05]

←-AT:PIEZOELECTRIC->