

OBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.


DPF

Pile Dynamics 17-Apr-15 06:25 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s NC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS*OP1 FR 20000 MB 30 DL -42 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1020	FS — BN 3349 10 SL 1450/ 3440/ 2 PJ: PN: HOPBAR TG F2 -- US A2 F2 3.3
---	--

TS 12	B PD: a20004	LP 0.00 ft
TB 8.0	T1 9.6 2L/C 4.7 UA 1000 UE 1022	LI 1.0

UMX= 4.6 FMX= 70 AMX= 139
 EMX= 0.3 MEX= 137 FUP= 0.99

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: A20004

CALIBRATION FACTOR: 1020 %

PAK (*5000): _____ DATE: 20APR15

PDA OPERATOR: M. Wright

<-AT:PIEZORESISTIVE OP: laine [ver:4.05] AT:PIEZOELECTRIC->

Smart Sensor

Smart Chip Programmed By M.W. on 20APR15 CRC Value B093