

Pile Dynamics 13-Nov-03 15:14		FS 10	BN 67 SL 2488/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3					
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s										
JC 0.40 FM 1.00 UM 1.00										
EA/C 30.3 Ks/ft UN KIPS 30.1 FR 20000 MB 30										
DL -48 UT 0 PK 1 TM-PEAK										
F1 500 F2 213 A1 999 A2 1230						TS 12 TB 8.0	E B PD: 9518 T1 8.7 2L/C 4.7	VA 1000 VE 1024	LP 0.00 ft LI 1.0	
ACCEPT SQ-OFF FL-OFF PR-OFF										
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916										
ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 9518 CALIBRATION FACTOR: 1230 G/V PAK-(*5000): _____ DATE: 13-Nov-03 PDA OPERATOR: <i>Fred Iver</i>										

UMX= 3.8 FMX= 61 AMX= 80
 EMX= 0.2 MEX= 119 FVP= 1.00

OP: fred Iver:4.051

<-AT:PIEZORESISTIVE >AT:PIEZOELECTRIC->