

File Dynamics 27-Feb-01 12:43	FS — 5	BN 272 SL 1606/ 3440/ 99	PJ: CALIBRATION PN: HOPBAR	TG U1 -- US A2 F2 61.9
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16815 ft/s WC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN <del>KIPS:0.1</del> FR 20000 MB 90	TS 12 U E BH PD: 9520 LP 0.00 ft FF-9 TB 7.0 T1 9.8 2L/C 4.7 UA 1000 <b>VE 1004</b> LI 1.0 UF-9			
DL -43 UT 0 PK 1 TM-PEAK	VMX= 32.7 FMX= 22 AMX= 1404 VT1= 0.5 MEX= 43 FVP= 0.02			
F1 500 F2 284 A1 1600 A2 880	ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 9520 CALIBRATION FACTOR: 17.6 G/V PAK (*5088): <i>[Signature]</i> DATE: 27-FEB-2001 PDA OPERATOR: <i>[Signature]</i>			

STANDBY SQ-OFF FL-OFF PR-OFF



contact File Dynamics USA  
with your questions  
tel USA - 216 - 831- 6131  
fax USA - 216 - 831- 0916

<-AT:PIEZORESISTIVE

OP: Ryan C. Allin [ver:4.051

AT:PIEZOELECTRIC->