

Pile Dynamics 10-Feb-00 15:30	FS —	BN 339 SL 1610/ 3440/ 99	PJ: CALIBRATION PN: HOPBAR	TG U1 -- US A2 F2 60.0
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16815 ft/s MC 16862 ft/s				
JC 0.40 FM 1.00 UM 1.00				
EA/C 30.3 Ks/ft UN KIPS/0 FR 20000 MB 90				
DL 0 UT 0 PK 1 TM-PEAK				
F1 500 F2 284 A1 1600 A2 855				
TS 12 U E BH PD: 9521 LP 0.00 ft TB 7.0 T1 11.9 2L/C 4.7 UA 1000 VE 1004 LI 1.0				

STANDBY SQ-OFF FL-OFF PR-OFF

VMX= 32.9 FMX= 24 AMX= 1843
 VT1= 27.9 MEX= 47 FVP= 0.02

contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 9521

CALIBRATION FACTOR: 17.1 G/v

PAK (*5000): DATE: 10-FEB-2000

PDA OPERATOR: Rode