

Pile Dynamics 10-Mar-04 15:29	FS — 10	BN 1006 SL 2607/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US 42 F2 3.3			
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s							
JC 0.40 FM 1.00 VM 1.00							
EA/C 30.3 Ks/ft UN KIPS=0.1 FR 20000 MB 30							
DL -42 VT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 1020							
TS 12 TB 8.0					E B PD: 10839 T1 9.6 2L/C 4.7	VA 1000	LP 0.00 ft LI 1.0
<b>VE 1024</b>							
UMX= 5.1 FMX= 78 AMX= 209 EMX= 0.4 MEX= 152 FVP= 1.00							
ACCEPT SQ-OFF FL-OFF PR-OFF							
ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 10839 CALIBRATION FACTOR: 1020 GIV PAK (*5000): _____ DATE: 10-Mar-04 PDA OPERATOR: Fred Houslin							

contact Pile Dynamics USA  
with your questions  
tel USA - 216 - 831- 6131  
fax USA - 216 - 831- 0916



<-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

AT:PIEZOELECTRIC->