

Pile Dynamics 12-Mar-04 13:41		FS 10	BN 1220 SL 2650/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS/0.1 FR 20000 MB 30	DL -39 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1000	TS 12 TB 8.0	B PD: 10845 T1 9.5	2L/C 4.7	UA 1000 UE 1024	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
 VMX= 4.3 FMX= 66 AMX= 139
 EMX= 0.3 MEX= 129 FUP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 10845
 CALIBRATION FACTOR: 1000 G/V
 PAK <X5000>: _____ DATE: 12-Mar-04
 PDA OPERATOR: Fred Hession

<-AT:PIEZORESISTIVE

OP: FRED Ever:4.051

AT:PIEZOELECTRIC->