

Pile Dynamics 22-Nov-04 09:39		FS — 10	BN 709 SL 2581/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS/IN FR 20000 MB 30					
DL -41 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1150	TS 12 TB 8.0	B PD: 10849 T1 9.2 2L/C 4.7	UA 1000 UE 1024	LP 0.00 ft LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 3.5 FMX= 56 AMX= 80
 EMX= 0.2 MEX= 109 FUP= 1.00

contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 10849
 CALIBRATION FACTOR: 1150 G/V
 PAK (#5000): DATE: 22 Nov 04
 PDA OPERATOR: *[Signature]*