

<b>Pile Dynamics</b> 12-Mar-04 13:28		FS — 10	BN 1208 SL 2645/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30					
DL -37 UT -1 PK 1 TM-PEAK					
F1 500 F2 213 A1 999 A2 1020	TS 12 TB 8.0	B PD: 10851 T1 9.6 2L/C 4.7	UA 1000 UE 1024	LP 0.00 ft LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 4.9 FMX= 76 AMX= 179  
 EMX= 0.3 MEX= 149 FUP= 1.00



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10851

CALIBRATION FACTOR: 1020 G/V

PAK <<5888>>: DATE: 12-Mar-04

PDA OPERATOR: Fred Thosain

<-AT:PIEZORESISTIVE

OP: FRED Iver:4.05]

[AT:PIEZOELECTRIC->