


Pile Dynamics 12-Mar-04 12:57		FS — 10	BN 1185 SL 2640/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 17043 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30	TS 12 B PD: 10852 LP 0.00 ft TB 8.0 T1 9.7 2L/C 4.7 VA 1000 UE 1024 LI 1.0				
DL -36 UT -1 PK 1 TM-PEAK	F1 500 F2 213 A1 999 A2 1005				

ACCEPT SQ-OFF FL-OFF PR-OFF
 VMX= 4.9 FMX= 77 AMX= 179
 EMX= 0.4 MEX= 150 FUP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 10852
 CALIBRATION FACTOR: 1005 61V
 PAK < *5000 > : DATE: 12-Mar-04
 PDA OPERATOR: Fred Hussain