

Pile Dynamics 12-Mar-04 13:38		FS — 10	BN 1213 SL 2648/ 3440/ 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30	DL -37 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1015	TS 12 TB 8.0	S T1 9.6	B PD: 10855 2L/C 4.7	UA 1000 UE 1024	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 4.4 FMX= 68 AMX= 149
 EMX= 0.3 MEX= 133 FUP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 10855
 CALIBRATION FACTOR: 1015 G/V
 PAK ←5000→: _____ DATE: 12-Mar-04
 PDA OPERATOR: Fred Hustin

←-AT:PIEZORESISTIVE

OP: FRED [ver:4.05]

▶AT:PIEZOELECTRIC▶