

QBTA: ON [ALT-F1/BB=60]

Pile Dynamics, Inc.

DPF

Pile Dynamics 20-Apr-15 05:01	FS — 10	BN 3617 SL 1521 / 3440 / 2	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3		
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s						
JC 0.40 FM 1.00 UM 1.00						
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30						
DL -39. UT -1 PK 1 TM-PEAK						
F1 500 F2 213 A1 999 A2 1000						
TS 12 TB 8.0					B PD: 10864-060 T1 9.6 2L/C 4.7 UA 1000 UE 1022	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF

VMX= 4.4 FMX= 68 AMX= 139  
EMX= 0.3 MEX= 133 FVP= 1.00



contact Pile Dynamics USA  
with your questions  
tel USA - 216 - 831- 6131  
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 10864

CALIBRATION FACTOR: 1000%

PAK (\*5000): DATE: 23 APR 15

PDA OPERATOR: M. Wright

<-AT:PIEZORESISTIVE

OP: Iaine [ver:4.051

AT:PIEZOELECTRIC->