

<b>Pile Dynamics</b> 11-Oct-04 14:07		FS — 10	BN 1384 SL 2741/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in <sup>2</sup> EM 30000 Ksi SP 0.492 K/ft <sup>3</sup> WS 16810 ft/s WC 16862 ft/s  JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN <del>KIPS</del> 0.1 FR 20000 MB 30  DL -42 UT -1 PK 1 TM-PEAK  F1 500 F2 213 A1 999 A2 990					
TS 12 B PD: 11030-060 LP 0.00 ft TB 8.0 T1 9.4 2L/C 4.7 UA 1000 UE 1024 LI 1.0					

ACCEPT SQ-OFF-FL-OFF PR-OFF  
 UMX= 4.9 FMX= 76 AMX= 159  
 EMX= 0.3 MEX= 149 FUP= 1.00



contact Pile Dynamics USA  
 with your questions  
 tel USA - 216 - 831- 6131  
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable  
 SERIAL NUMBER: 11030  
 CALIBRATION FACTOR: 990 GIV  
 PAK (3000): \_\_\_\_\_ DATE: 11-Oct-04  
 PDA OPERATOR: *Jamal Hussein*