

QBTA: ON IALT-F1/BB=60J

Pile Dynamics, Inc.

DPF

Pile Dynamics
04-May-15 05:06

FS —
10

BN 4549
SL 1826/ 3440/ 99

PJ:
PN: HOPBAR

TG F2 -- US
A2 F2 3.3

LE 39.6 ft
AR 1.7 in2
EM 30000 Ksi
SP 0.492 K/ft3
WS 16810 ft/s
WC 16862 ft/s

JC 0.40
FM 1.00
UM 1.00

EA/C 30.3 Ks/ft
UN KIPS*0.1
FR 20000 MB 30

DL -40
UT -1
PK 1 TM-PEAK

F1 500
F2 213
A1 999
A2 1035

TS 12 B PD: 11035-060 LP 0.00 ft
TB 8.0 T1 9.6 2L/C 4.7 VA 1000 UE 1022 LI 1.0

UMX= 4.5 FMX= 69 AMX= 149
EMX= 0.3 MEX= 135 FUP= 0.99

ACCEPT SQ-OFF FL-OFF PR-OFF



contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable

SERIAL NUMBER: 11035

CALIBRATION FACTOR: 1035 %

PAK (*5000): DATE: 7 MAY 15

PDA OPERATOR: *[Signature]*

<-AT:PIEZORESISTIVE

OP: Iaine Iver:4.051

AT:PIEZOELECTRIC->