

Pile Dynamics 22-Apr-04 15:36		FS — 10	BN 393 SL 2539/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3				
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 VM 1.00 EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30 DL -37 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 998					TS 12 TB 8.0	E B PD: 11040 T1 9.6 2L/C 4.7	UA 1000 UE 1024	LP 0.00 ft LI 1.0	

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 4.6 FMX= 71 AMX= 169
 EMX= 0.3 MEX= 139 FUP= 1.00

contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11040
 CALIBRATION FACTOR: 998 G/V
 PAK (*5888): _____ DATE: 22-Apr-04
 PDA OPERATOR: Fred Moser