


Pile Dynamics 22-Apr-04 15:33		FS — 10	BN 387 SL 2539/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN KIPS:0.01 FR 20000 MB 30	DL -40 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1015	TS 12 TB 8.0	E B PD: 11043 T1 9.5 2L/C 4.7	VA 1000 UE 1024	LP 0.00 ft LI 1.0	

~~ACCEPT~~ SQ-OFF FL-OFF PR-OFF
 UMX= 4.3 FMX= 67 AMX= 149
 EMX= 0.3 MEX= 131 FUP= 1.01



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11043
 CALIBRATION FACTOR: 1015 6IV
 PAK (*5000): _____ DATE: 22-Apr-04
 PDA OPERATOR: Fred Thornein