

File Dynamics 28-Apr-04 14:16 LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s JC 0.40 FM 1.00 UM 1.00 EA/C 30.3 Ks/ft UN KIPS 30.3 FR 20000 MB 30 DL -39 UT -1 PK 1 TM-PEAK F1 500 F2 213 A1 999 A2 1007	FS — BN 47 SL 2493/ 3440/ 99 PJ: PN: HOPBAR TG F2 -- US A2 F2 3.3 TS 12 E B PD: 11046 LP 0.00 ft TB 7.0 T1 9.3 2L/C 4.7 UA 1000 UE 1022 LI 1.0
--	---

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 3.7 FMX= 58 AMX= 110
 EMX= 0.3 MEX= 113 FVP= 1.00



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11046
 CALIBRATION FACTOR: 1007 G/V
 PAK (*5000): DATE: 28 Apr. 04
 PDA OPERATOR: *[Signature]*