

File Dynamics 11-Sep-08 09:46	FS — 10	BN 473 SL 2773/ 3440/ 99	PJ: sn PN: HOPBAR	TG F2 -- US A2 F2 3.3			
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s							
JC 0.40 FM 1.00 UM 1.00							
EA/C 30.3 Ks/ft UN KIPS=30.1 FR 20000 MB 30							
DL -26 UT -1 PK 1 TM-PEAK							
F1 500 F2 213 A1 999 A2 1015							
TS 12 TB 8.0					B PD: 11047-060 T1 9.6 2L/C 4.7	UA 1000	LP 0.00 ft LI 1.0
UMX= 3.8 FMX= 60 AMX= 139 EMX= 0.2 MEX= 117 FUP= 1.00							
ACCEPT SQ-OFF FL-OFF PR-OFF							
ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 11047 CALIBRATION FACTOR: 1015 G/V PAK (*5000): DATE: 11-SEP-08 PDA OPERATOR: <i>[Signature]</i>							
<-AT:PIEZORESISTIVE OP: alex [ver:4.05] AT:PIEZOELECTRIC->							

contact Pile Dynamics USA
with your questions
tel USA - 216 - 831- 6131
fax USA - 216 - 831- 0916



[Handwritten circle]